

decordna

Product Specifications

Description: Heavy duty ribbed carpet especially suited for non slip environments

Suitability: Commercial, marine, education, ramps, walkways, entranceways, mats

Product Benefits: Extensive colour range, design freedom with inlays, borders and logos, will not rot, fade resistant, lifetime anti-run and anti-fray warranties, UV Stabilised to minimise the effects of fading (please refer to warranty sheet)

Fibre: 100% polypropylene fibre

Total Product Weight: 1260gsm

Total Nominal Thickness: 7mm

Product Width: 2 metres

Roll Length: 25 metres

Moisture Absorption: 0.006%, will not rot or smell

Fire Ratings:

AS1530 Part 3:

Spread of Flame (Index 0-10) 0

Smoke Developed (Index 0-10) 5

- Tested June 1996, Applied Physics Laboratory (APL)

ISO 9239

Average Critical Radiant Flux: 5.0kW/m²

Average Smoke Obscuration: 379%. min

- Tested September 2004, CSIRO

Care and Maintenance: Ask your local distributor for an Autex Carpet Care and Maintenance brochure, or download a copy from our website

Installation: We recommend all Autex Carpets to be installed in accordance with AS/NZS:2455.1.2007 Textile floor coverings - installation practice. Ask your local distributor for an Autex Carpet Installation brochure, or download a copy from our website.

Quality Standards: Manufactured under ISO 9001 International Quality Standards

General: Test result certificates are available upon request. All Decord colours are available in Widetrack rib finish (subject to minimum order quantities). For further information about our complete range of quality carpet, contact your local distributor or visit our website.

AUTEX



Autex Industries Ltd

702 - 718 Rosebank Rd
Private Bag 19988,
Avondale 1746, Auckland
New Zealand
Phone +64 9 828 9179
Fax +64 9 828 5810
Freephone 0800 428 839
www.autex.co.nz

