



Product Specifications

Description: Create unique designs by using Elements flat pile carpet. Available in either roll form or self-adhesive tiles, Elements is ideal for defining pathways or cutting in designs and logos

Suitability: Commercial, garages, education, retail and healthcare

Product Benefits: Extensive colour range, design freedom with inlays, borders and logos, will not rot, lifetime anti-run and anti-fray warranties

Fibre: 100% polypropylene fibre

Total Product Weight: 900gsm

Total Nominal Thickness: 4mm

Product Width: 2 metres

Roll Length: 25 metres

Tile Size: 500mm x 500mm

Tile Coverage:

Self adhesive tile - 10 tiles per pack - 2.5m²

Non adhesive backed tile - 20 tiles per pack - 5.0m²

Moisture Absorption: 0.006% will not rot or smell

Fire Ratings:

AS1530 Part 3:

Spread of Flame (Index 0-10) 2

Smoke Developed (Index 0-10) 5

-Tested 22 January 1999, Applied Physics Laboratory (APL)

AS/ISO 9239 Part 1:

Average Critical Radiant Flux: 6.6 kW/m²

Average Smoke Obscuration: 369%.min

-Tested 18 August 2003, CSIRO

Care and Maintenance: Ask your local distributor for an Autex Carpet Care and Maintenance brochure, or download a copy from our website

Installation: Ask your local distributor for an Autex Carpet Installation brochure, or download a copy from our website

Quality Standards: Manufactured to ISO 9001 International Quality Standards

General: Test result certificates and terms of warranty are available upon request. For further information about our complete range of quality carpet, contact your local distributor or visit our website

AUTEX



Autex Industries Ltd

702 - 718 Rosebank Rd
Private Bag 19988,
Avondale 1746, Auckland
New Zealand
Phone +64 9 828 9179
Fax +64 9 828 5810

Freephone 0800 428 839
www.autex.co.nz