



Product Specifications

Description: Performer and Flex are ideally suited to the marine and automotive industry as hull or wall linings. Performer is a latex backed product giving extra rigidity while Flex is non backed and designed to be easily moulded into place

Suitability: Marine and Automotive trim and linings

Product Benefits: Extensive colour range, will not fade or rot, lifetime anti-run and anti-fray warranties

Fibre: 100% Polypropylene fibre

Backing: Performer - SBR Latex, Flex - unbacked

Total Product Weight: Performer - 800gsm, Flex - 425gsm

Total Nominal Thickness: Performer - 5mm, Flex - 5mm

Product Width: 2 metres

Roll Length: 25 metres

UV Stabilised: Limited Outdoor - please refer to warranty sheet

Moisture Absorption: 0.006% will not rot or smell

Fire Ratings:

AS1530 Part 3:

Performer:

Ignitability (Index 0-20) 15

Heat Evolved (0-10) 5

Spread of Flame (Index 0-10) 6

Smoke Developed (Index 0-10) 4

-Tested August 2002, CSIRO

Flex:

Ignitability (Index 0-20) 14

Heat Evolved (0-10) 5

Spread of Flame (Index 0-10) 6

Smoke Developed (Index 0-10) 3

-Tested August 2002, CSIRO

Care and Maintenance: Ask your local distributor for an Autex Carpet Care and Maintenance brochure, or download a copy from our website

Installation: Ask your local distributor for an Autex Carpet Installation brochure, or download a copy from our website

Quality Standards: Manufactured to ISO 9001 International Quality Standards

General: Test result certificates are available upon request. For further information about our complete range of quality carpet, contact your local distributor or visit our website

AUTEX



Autex Industries Ltd

702 - 718 Rosebank Rd
Private Bag 19988,
Avondale 1746, Auckland
New Zealand
Phone +64 9 828 9179
Fax +64 9 828 5810

Freephone 0800 428 839
www.autex.co.nz