



# WIDETRACK

## Product Specifications

**Description:** A stylish, hard wearing ribbed carpet

**Suitability:** Commercial, marine, education and retail

**Product Benefits:** Extensive colour range, design freedom with inlays, borders and logos, will not rot, fade resistant, lifetime anti-run and anti-fray warranties, UV Stabilised to minimise the effects of fading (please refer to warranty sheet)

**Fibre:** 100% polypropylene fibre

**Total Product Weight:** 1260gsm

**Total Nominal Thickness:** 7mm

**Product Width:** 2 metres

**Roll Length:** 25 metres

**Moisture Absorption:** 0.006%, will not rot or smell

### Fire Ratings:

AS1530 Part 3:

Spread of Flame (Index 0-10) 0

Smoke Developed (Index 0-10) 5

- Tested June 1999, Applied Physics Laboratory (APL)

Average Critical Radiant Flux: 4.9kW/m<sup>2</sup>

- Tested September 2004, CSIRO

**Care and Maintenance:** Ask your local distributor for an Autex Carpet Care and Maintenance brochure, or download a copy from our website

**Installation:** We recommend all Autex Carpets to be installed in accordance with AS/NZS:2455.1.2007 Textile floor coverings - installation practice. Ask your local distributor for an Autex Carpet Installation brochure, or download a copy from our website.

**Quality Standards:** Manufactured under ISO 9001 International Quality Standards

**General:** Test result certificates are available upon request. All Widetrack colours are available in Decord rib finish (subject to minimum order quantities). For further information about our complete range of quality carpet, contact your local distributor or visit our website.

**AUTEX**



**Autex Industries Ltd**

702 - 718 Rosebank Rd  
Private Bag 19988,  
Avondale 1746, Auckland  
New Zealand  
Phone +64 9 828 9179  
Fax +64 9 828 5810  
Freephone 0800 428 839  
www.autex.co.nz